



Brüel & Kjær Vibro



VIBROCONTROL 1100

**The 2 x 2 solution for bearing vibration and
rolling-element bearing condition**

VIBROCONTROL 1100

reliably helps prevent machine damage and production downtime. These objectives are reached when

- the actual condition of the machine and its components are continuously measured,
- irregularities in the operating condition are signalled at an early stage and
- reaching a dangerous operating condition results in an immediate shutdown of the machine.



Bearing vibrations

Through measurement of the mechanical vibrations in the frequency range up to 1000 Hz and comparison of the measured values with

- Standards and guidelines,
- Default values from the machine manufacturer or
- Values determined by experience

decisions can be made about the overall machine condition. Faults such as rotor unbalance, alignment errors, foundation movements, blade and gear damage can be identified in this way at an early stage.

Rolling-element bearing condition

Impulses caused by rolling-elements are a measure of the rolling-element bearing condition. Reliable monitoring of the rolling-element bearing condition is possible through

- Measurement of the intensity and regularity of the impulses,
- Formation of a special characteristic value, namely and Bearing Condition Unit (BCU) and
- Normalized BCU values

Damage and production downtime as a result of “defective” bearings can be prevented with a high degree of accuracy.

VIBROCONTROL 1100 consists of the component vibration sensors and electronic monitoring instrument.

Vibration sensor

Mechanical vibrations and impulses which occur at the machine are converted by the vibration sensors into electrical signals. According to the monitoring task, acceleration or vibration velocity sensors can be used.

Monitoring electronics

The monitoring electronics has 2 sensor inputs and carries out the vibration and bearing condition measurements at two separate signal paths.

According to the operating mode and measurement type, cycle times of 0.25 secs for single-channel and 6...20 secs for 2-channel operation can be achieved. For each channel, 2 limit values for vibration and 1 limit value for bearing condition can be set up. The alarm relay delay time is individually selectable for each limit value signal.

VIBROCONTROL 1100
2 analogue outputs. The assignment of the measurements to the analogue outputs and their operating mode

can be freely programmed.

3 limit value relays with potential-free contacts for signalling limit value violations. The OK-relay signals the condition of the sensors, cable and power supply.

The operator can be directly informed at the instrument about the current measurements, limit value violations, relay conditions and Logbook entries.

The Logbook represents a ring memory with max. 99 entries for the storage of events, e.g. limit value violations, OK-faults, power failures.

Reliability

An internal, system-testing software, automatic self-calibration and protective circuits such as

- Self-monitoring
- Limit value blocking
- Power-up error protection

provide a guarantee of trouble-free operation of the instrument.

- Plug-in connection terminals
- Rugged industrial housing in IP-65 protection class
- Selectively 1 or 2 acceleration or vibration velocity sensors in industrial design.

Setting up the monitoring electronics

Directly at VIBROCONTROL 1100

All settings can be carried out directly at the instrument and edited at any time through the user-friendly dialogue. The instrument has a built-in LCD display and 5 operating pushbuttons.

VIBROCONTROL 1100 Technical Data

  		2-channel bearing vibration and 2-channel bearing condition	
Order code VC-1100-Cxx	Type C01 Bearing vibration and bearing condition 230/115 V AC, 50/60 Hz, approx. 15 VA C02 Bearing vibration and bearing condition 24 V DC (16...36 V), appr. 15 W C11 Bearing vibration 230/115 V AC, 50/60 Hz, appr. 15 VA C12 Bearing vibration 24 V DC (16...36 V), appr. 15 W		
Inputs No. of vibration channels Sensor connections Sensor power Sensor OK monitoring	2 Acceleration sensor, e.g. AS-022, AS-062, (CCS), ASA-022 etc. Vibration velocity sensor, e.g. VS-068, VS-069, VS-0168, VC-0169 -24 V DC (max. 30 mA) or 4 mA constant-current power (CCS) ^{^)} Velocity sensor : no power required Yes		
Measurement types^{†)} Measurement channels (operating modes) Frequency range Vibration displacement ^{†)} Bearing vibration measurement Bearing condition measurement Measurement accuracy	1-channel operation with continuous monitoring 2-channel operation with cyclic monitoring Cycle time appr. 6...20 sec. Standard setting 10 Hz to 1 kHz Highpass: 1, 3, 10 Hz; Lowpass: 1 kHz, 10 kHz Integrated vibration velocity signal (10 Hz – 1 kHz) in μm RMS value of vibration velocity in mm/s Signal detection selectable: RMS, peak value, peak-peak value RMS value of acceleration in mm/s^2 Signal detection selectable: RMS, peak value (p), peak-peak value (p-p) BCU (Bearing Condition Unit) Bearing vibration 2% of measured value Bearing condition +/- 6% of measured value and +/- 3.5% of measuring range full scale value		
Monitoring^{†)} Alarm signalling Alarm relay delay time Alarm relays	Alert and Danger alarms for bearing vibrations and one alarm for bearing condition 1...99 sec. 3 relays with free assignment to measurement type, with AND/OR coupling, normally-energized or normally de-energized operation, latching or non-latching		
Outputs^{†)} Analogue signal outputs Measured signal outputs	The function can be assigned to one of the measurement types: 0/4...20 mA (Load $\leq 500 \Omega$) or 0...10 V (Load $\geq 1 \text{ k}\Omega$) Phase-correct data (Buffered output) of the sensor signal		
Power supply Mains power	230/115 V AC +15% / - 25%, 50/60 Hz, appr. 15 VA 24 V DC (16...36 V), appr. 15 W		
Environmental conditions Operating temperature range Storage temperature range Humidity	0°C...+ 50°C - 20°C...+ 70°C Max. 95% non-condensing		
Mechanical data Housing Dimensions Cable feed	Rugged aluminium housing in IP-65 protection class. Total weight appr. 5 kg 400 x 160 x 91 mm (L x B x H) 3 x M 20 x 1.5 and 9 x M 16 x 1.5 feed-through fittings		

^{†)} Each channel and connected sensor

^{^)} only with acceleration sensors with constant-current power (CCS)

^{‡)} only with vibration velocity sensors

Order data for VIBROCONTROL 1100 and accessories		
VC-1100 Monitoring electronics	Type C01	For vibration and bearing condition, Power supply 230/115 V AC, 50/60 Hz
	Type C01 CCS	For vibration and bearing condition, Power supply 230/115 V AC, 50/60 Hz ¹⁾
	Type C02	For vibration and bearing condition, Power supply 24 V DC
	Type C02 CCS	For vibration and bearing condition, Power supply 24 V DC ¹⁾
	Type C11	For vibration only, Power supply 230/115 V AC, 50/60 Hz
	Type C11 CCS	For vibration only, Power supply 230/115 V AC, 50/60 Hz ¹⁾
	Type C12	For vibration only Power supply 24 V DC
	Type C12 CCS	For vibration only Power supply 24 V DC ¹⁾
Installation accessories like:	AC-2104	Terminal protective housing for max. 2 vibration sensors, standard
	AC-2105	Terminal protective housing for max. 2 acceleration sensors, Ex-protection (Exi)
	AC-2103	Terminal protective housing for max. 2 velocity sensors, Ex-protection (Exe)
	AC-112	Signal cable, shielded, 4 x 0.5 mm ² , for acceleration sensor
	AC-114	Signal cable, shielded, 4 x 0.5 mm ² , for acceleration sensor, Ex protection (Exi)
	AC-186	Signal cable, shielded, 2 x 0.75 mm ² , for velocity sensor, Ex protection (Exe)
	AC-2201	PU-sheathed steel protective conduit, minimum order length 5 m
	AC-2202	Protective conduit fittings M 12 x 1.5, delivery extent: 2 pieces
	AC-2304/16/12	Reducers for protective conduit fittings from M 16 x 1.5 to M 12 x 1.5; 10 pieces
	AC-352	Mounting bolt for acceleration sensors
	AC-354	Stepped drill for mounting bolts
Acceleration sensors	AS-022	Any measurement direction, 5 m cable with central threaded mounting hole
	ASA-022	Any measurement direction, 5 m cable, Ex-protection II 2G Ex ia IIC T6/ II 2D Ex iaD 21 T=145°C ²⁾
	AS-030	Any measurement direction, without cable, with Fast-On lugs, with protective cap
	AS-062 (CCS)	Any measurement direction, 5 m cable with central threaded mounting hole
	ASA-062 (CCS)	Any measurement direction, 5 m cable with central threaded mounting hole ²⁾
Velocity sensors	VS-068	For horizontal measurement, 5 m cable
	VS-069	For vertical measurement, 5 m cable
	VS-0168	For horizontal measurement, 10 m cable, Ex protection II 2G Ex d IIC T6/ II 2D Ex tD A21 IP66 T=85°C ²⁾
	VS-0169	For vertical measurement, 10 m cable, Ex protection II 2G Ex d IIC T6/ II 2D Ex tD A21 IP66 T=85°C ²⁾
Accessories for Ex protection	AC-293	Safety barriers, complete for one acceleration sensor ASA-02x with Ex protection

Accessories for computer connection and network operation, e.g. interface converters, special cables, over-voltage protection equipment and further installation accessories on enquiry.

¹⁾ only with acceleration sensor with constant-current power (CCS)

²⁾ ATEX certificates and datasheets are available on our homepage for download

Brüel & Kjær Vibro A/S

Skodsborgvej 307B
2850 Nærum
Denmark
Tel.: +45 77 41 25 00
Fax: +45 45 80 29 37
info@bkvibro.com

Brüel & Kjær Vibro GmbH

Leydheckerstraße 10
64293 Darmstadt
Germany
Tel.: +49 (0) 6151 428 11 00
Fax: +49 (0) 6151 428 12 00
info@bkvibro.de

www.bkvibro.com